BCM400D-KNX Motorized Curtain Kit User Manual

Motor								
Model	BCM400D-KNX							
Name	Smart KNX Motorized Curtain							
Torque	1.2NM							
Voltage	AC100V-240V 50/60HZ							
Power	40W							
Load	50kg Maximum							
Interface	KNX, Remote Control							
Function	Open/Close/Pause/Percentage Control/Feedback/Direction Shift							
Certificate	CE and KNX							
Protection	IP20, CLASS F							
Power Plug	EU/US/AU/UK Type							
Programming Software	ETS5							
Dimension	50mm*50mm*270mm							
Product Picture								
Remote Controller								
Model	BE301							
Name	Single Channel Handheld Remote Controller							
Battery	2*1.5V AAA Battery							
Transmit Frequency	433.92MHz							
Transmit Power	≤10mW							
Temperature	-10°C~50°C							
Distance	50meters							

Produc Picture	t										
					Curt	ain Tra	ack				
Materia	al	Aluminum Profile									
Surface treatme		Electrophoresis Silver									
Track Cross S	ection	41.50									
Load	Load Maximum 50kg(If track length less than 4meters) Maximum 35kg(If track length more than 4meters)										
				Mo	otorize	ed Cur	tain Ki	t			
Мо	toriz	zed o	urta	in tr	ack	kit s	pec	ificat	ions		
NO.	Size	Track Length (mm) 1000	Track Connector (mm) 100	Tracl 500	Adjustable Track Track Length (mm) 500 200 100			onnector m) 100	Suitable Size(M) (Wall To Wall)		
1	2.2m	1	1	1	2	1	1	1	Under2.2m		
2	3.2m	2	2	1	2	1	1	1	2.2m-3.2m		
3	4.2m	3	3	1	2	1	1	1	3.2m-4.2m		
4	5.2m	4	4	1	2	1	1	1	4.2m-5.2m		
5	6.2m	5	5	1	2	1	1	1	5.2m-6.2m		
6	7.2m	6	6	1	2	1	1	1	6.2m-7.2m		
7 Note:						table trac		1 m,100mm	7.2m-8.2m are track connectors		
Dimension		1050m	1050mm*230mm*80mm(2.2m-5.2m) 1050mm*300mm*80mm(6.2m-8.2m)								
Parts In	clude		Track, T Bracket				e Contro	oller, Gear	Box, Carrier, Runners, Belts,		