

Product data sheet

Specifications



SpaceLogic KNX USB Interface DIN Rail

MTN6502-0101

Main

Range	SpaceLogic KNX
Product or component type	USB interface
Bus type	KNX
Colour tint	Schneider white
Colour code	RAL 9003
Market segment	Residential Commercial

Complementary

Connector type	USB type C
Communication port protocol	USB KNX KNX long frame
Transmission rate	12 Mbit/s 9600 bit/s
Total number of 18 mm modules	1
Local signalling	2 LEDs
Material	PC
Mounting support	DIN rail
Function available	Supports KNX Secure

Environment

Relative humidity	5...93 %
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-5...45 °C

Standards	EMC directive EN 50491-3 EN 50491-5-2 EN 50491-5-3 EN 61000-6-2 EN 61000-6-3 EN 50581 : 2012
-----------	--

IP degree of protection	IP20
-------------------------	------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	7.0 cm
Package 1 Length	9.5 cm
Package 1 Weight	82.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.717 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)